

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
30 October 2003 (30.10.2003)

PCT


(10) International Publication Number  
**WO 03/089755 A1**

- (51) International Patent Classification<sup>7</sup>: **E21B 21/10, 43/10, 34/12**
- (21) International Application Number: **PCT/GB03/01596**
- (22) International Filing Date: **14 April 2003 (14.04.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
**0208673.4** **16 April 2002 (16.04.2002)** **GB**
- (71) Applicant (for all designated States except US): **SPECIALISED PETROLEUM SERVICES GROUP LIMITED** (GB/GB); Arnhall Business Park, Westhill, Aberdeen AB32 6TQ (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **CARMICHAEL,**
- Mark (GB/GB): **Douet de Rne, St Mary, Jersey JE3 3EF (GB).**
- (74) Agent: **KENNEDYS PATENT AGENCY LIMITED;** Queens House, Floor 5, 29 St. Vincent Place, Glasgow G1 2DT (GB).
- (81) Designated States (*national*): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (*regional*): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,**

[Continued on next page]

(54) Title: **CIRCULATING SUB**

(57) Abstract: A control sub for use with a hydraulically operated downhole tool. In an embodiment, the sub comprises an outer sleeve connected to a work string and an inner sleeve slidably engaged to the outer sleeve by matching hex profiles, connected to the downhole tool. Radial ports in the outer sleeve provide selective circulation of fluid from the tool and by closing these ports with the sleeve fluid pressure in to the downhole tool can be controlled. Closure is effected by setting down weight on the sub against the tool. An indexing mechanism is also described to keep the tool in a configuration, which maintains pressure on the tool. The sub is suitable for use with an expander tool.



WO 03/089755 A1

WO 03/089755 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— with international search report